



Wilson High School Lighting Fixture Schedule 14 September 2009			mcla ARCHITECTURAL LIGHTING DESIGN	
Type	Mounting	Lamps	Manufacturer and Series	Notes
PM202-3	Trellis Pendant	<3> CMH/PM202-3L30SP Constant Color CMH by G.E.	ALM T.B.D.	Pendant mount air. Multiple metal halide PAR20, adjustable downlights. Looking pan and IR. Black Alzak reflectors. Integral remote for beamwing system. Accessory holders. Prismatic diffusion accessory lenses. Prismatic overall spread accessory lenses. - Install with prismatic diffusion accessory lenses. Provide spread lenses for use by Lighting Consultant during aiming. location(s): courtyard canopy
PM202-4	Trellis Pendant	<4> CMH/PM202-4L30SP Constant Color CMH by G.E.	ALM T.B.D.	Pendant mount air. Multiple metal halide PAR20, adjustable downlights. Looking pan and IR. Black Alzak reflectors. Integral remote for beamwing system. Accessory holders. Prismatic diffusion accessory lenses. Prismatic overall spread accessory lenses. - Install with prismatic diffusion accessory lenses. Provide spread lenses for use by Lighting Consultant during aiming. location(s): courtyard canopy
PM202-6	Trellis Pendant	<6> CMH/PM202-6L30SP Constant Color CMH by G.E.	ALM T.B.D.	Pendant mount air. Multiple metal halide PAR20, adjustable downlights. Looking pan and IR. Black Alzak reflectors. Integral remote for beamwing system. Accessory holders. Prismatic diffusion accessory lenses. Prismatic overall spread accessory lenses. - Install with prismatic diffusion accessory lenses. Provide spread lenses for use by Lighting Consultant during aiming. location(s): courtyard canopy
RC11	Ceiling Recessed	<1> FL-T 30/304P/ALTO by Philips	Intense Housing IF4 28 E 3rm IC482 HVC SF 58	Recessed compact fluorescent downlight. Diffused Alzak self-shielded 4" aperture reflector. Regressed frosted lens. location(s): courtyard portico
R01	Trellis Recessed	n/a	MP Lighting LED03 1 BL 140 FR 0 P 1" Finish	Recessed LED downlight. Remote power supply. - Connect remote power supply in accessible, ventilated location(s). location(s): courtyard canopy
S01	Wall Slot Surface	n/a	Optimum ML 10 250K x 1' length MC	Surface mount linear LED wall graze. Outdoor housing. Remote power supply, 10 degree optics. 3000K color temperature. - Connect remote power supply in accessible, ventilated location(s). location(s): courtyard wall slots
S02	Surface	n/a	Prosume XLA length U WWB	Surface mount linear LED end light. Extruded aluminum channel. Remote power supply, 3000K color temperature. - Connect remote power supply in accessible, ventilated location(s). - Contractor to provide lighting plans and field measurements to Manufacturer in order to coordinate required segmentation of fixture where used in curved runs. location(s): front walls

Wilson High School
Lighting Fixture Schedule
4 September 2009

ARCHITECTURAL LIGHTING DESIGN

Wilson High School
Lighting Fixture Schedule
4 September 2009

ARCHITECTURAL LIGHTING DESIGN

Type	Mounting	Lamps	Manufacturer and Series	Notes
X3M1	Fixing Integrated	10/2	Visual Lighting Technologies	<p>Metal halide floor optic system. End emitting floor to be integrated in paving in randomized star pattern. Spinkle wheel.</p> <p>- Conceal luminaires in accessible, ventilated location. - Provide 400 and 80 points. - Provide wet location above grade enclosure. - Location in enclosed spaces: 1' dryer</p>